



BI ENDURA

STABLE & PERFORMANT

Fully controllable from a **touch screen**, it is the most economical injector of the line in terms of workstation and produces around **4000 small and medium sized pieces** per day with the help of **one or two operators**.

The BI ENDURA injector combines an aggressive design with an essential line, which characterizes and enhances its **strength and sturdiness**, resulting in a machine with a slender line with two workstations.

The electronics reduced to a minimum, an interface with industrial touch screen, easy maintenance and powder-coated aluminum and stainless-steel surfaces make this injector particularly **reliable and suitable even for the most difficult environments**.

It is equipped with **two non-expandable independent stations**, a transparent melting tank with a constant vacuum system, a vacuum switch to check the vacuum in the mold, RFID readers, 8-cmc injection syringes with final temperature regulation and self-centering clamps with 120x90mm plates.

TECHNICAL SPECIFICATIONS



Moulds
Min 50x30x12 mm
Max 120x90x47 mm



Machine
54 kg
90x38x53 cm




Box
85 kg
123x50x70 cm

COMPATIBLE ACCESSORIES



Big Clamps
135x135 cm
140x180 cm
160x180 cm



Plates
120x120 cm
120x130 cm



Syringe 32 cmc



Double pump



Double steel tank



Touch Screen 7'

WATCH THE VIDEO

CHARACTERISTICS AND COMPONENTS

- PURE ITALIAN TECHNOLOGY
- 3 YEAR WARRANTY
- DOUBLE WORKING STATION
- HIGH PRODUCTION
- CUSTOMIZABLE MODELS
- INTERCHANGEABLE CLAMPS
- DIFFERENT SIZE OF MOULDS
- BIG CLAMPS
- RFID MICROCHIPS
- COLOR TOUCH SCREEN
- ANALOG VACUUM SWITCH
- ENDURANCE