

A small and compact injector with a non-expandable workstation fully controllable from a touch screen. It is able to produce around 2000 small and medium sized pieces per day with the help of only one operator.

The MONO ENDURA injector combines an aggressive design with an essential line, which characterizes and enhances its strength and sturdiness, resulting in a machine with a slender line with one

The electronics reduced to a minimum, an interface with industrial touch screen, easy maintenance and powder-coated aluminum and stainless-steel surfaces make this injector particularly reliable and suitable even for the most difficult environments

It is equipped with a transparent melting tank with a constant vacuum system, a vacuum switch to check the vacuum in the mold, an RFID reader, an 8-cmc injection syringe with final temperature regulation and a self-centering clamp with 120x90mm plates.

TECHNICAL SPECIFICATIONS



Moulds Min 50x30x12 mm Max 120x90x47 mm



Machine 38 kg 60x36x53 cm



67 kg 83x50x70 cm

COMPATIBLE ACCESSORIES



Big Clamps 135x135 cm 140x180 cm 160x180 cm



Plates 120x120 cm 120x130 cm



Syringe 32 cmc



Touch Screen 7'

WATCH THE VIDEO

CHARACTERISTICS AND COMPONENTS



PIIRE ITALIAN TECNOLOGY



3 YFAR WARRANTY



HIGH PRODUCTION



CUSTOMIZABLE MODELS



INTERCHANGEABLE



DIFFFFRENT SIZE OF MOULDS





MICROCHIPS



TOUCH SCREEN



ANALOG VACUUM SWITCH



ENDURANCE